

# CLM FOR PRIMACY



## THE IDEAL MODULE FOR LAMINATING AND PROTECTING YOUR CARDS

Developed by Evolis, the CLM (Card Lamination Module) module is associated with the Evolis Primacy printer and is an all-in-one system for printing, encoding, and laminating all cards that need to be secure and/or protected. ID cards made using CLM can be used for up to 10 years<sup>1</sup> and cannot be forged.

### EASY TO USE

- The CLM module is connected to the Primacy printer through infrared, forming a single system. Without replacing your printer, you can easily equip it with a lamination station.
- The films are installed intuitively and all the laminates are automatically recognized by CLM and Primacy.

### PRODUCTIVITY ASSURED

- CLM and Primacy encode the cards (magnetic strip, contact or contactless smart cards), print them in D2T2, and laminate them in a single operation.
- The printing and lamination modules work in parallel and produce up to 215 printed and laminated single-sided cards or 110 double-sided cards per hour.
- The CLM module can laminate double-sided cards as standard.

### WIDE CHOICE OF LAMINATES

- Evolis has a wide range of patches and laminates, with or without holograms.
- Our teams can develop personalized laminates on demand and as part of a specific project.
- All our patches and varnishes are high capacity and offer great system autonomy.

---

#### Applications :

- National ID cards
  - Driver's licenses
  - Secure access cards
  - Health cards
- 



## MAIN FEATURES / Full technical specifications on [www.evolis.com](http://www.evolis.com)

<b>GENERAL FEATURES</b>	<ul style="list-style-type: none"> <li>• Single and double sided lamination in standard</li> <li>• Standard built-in card flattener</li> </ul>
<b>LAMINATION PERFORMANCES<sup>1</sup></b>	<ul style="list-style-type: none"> <li>• Single side: up to 215 cards/hour</li> <li>• Dual side: up to 110 cards/hour</li> </ul>
<b>CARD MANAGEMENT AND SPECIFICATIONS</b>	<ul style="list-style-type: none"> <li>• Feeder capacity (from Primacy): 100 cards (0.76 mm - 30 mil)</li> <li>• Output hopper capacity: 100 cards (0.76 mm - 30 mil)</li> <li>• Reject tray capacity (from Primacy): 100 cards (0.76 mm - 30 mil)</li> <li>• Card thickness: 0.76 mm (30 mil)</li> <li>• Card types: PVC cards, composite PVC cards, PET cards, polycarbonate cards, special varnished cards</li> <li>• Card format: ISO CR80 - ISO 7810 (53.98 mm x 85.60 mm)</li> </ul>
<b>INTERFACES</b>	<ul style="list-style-type: none"> <li>• Infrared (no cable): connection kit with Primacy included</li> </ul>
<b>SAFETY</b>	<ul style="list-style-type: none"> <li>• Support for Kensington® security lock</li> </ul>
<b>DISPLAY</b>	<ul style="list-style-type: none"> <li>• Printer LEDs</li> <li>• Graphical notifications: cleaning alerts, empty/low level ribbon, etc</li> <li>• LCD screen as an option (factory installed)<sup>2</sup></li> </ul>
<b>EVOLIS HIGH TRUST® FILMS</b> To maximize the quality and durability of printed cards, the lifespan of the print head and lamination module reliability, use Evolis High Trust® films.	<ul style="list-style-type: none"> <li>• Automatic identification and setting</li> <li>• Color matching for easy installation</li> <li>• Available films: <ul style="list-style-type: none"> <li>- Clear patch (0.5 ou 1.0 mil): 600 sides / roll</li> <li>- Holographic Patch (0.6 ou 1.0 mil): 600 sides / roll</li> <li>- Patch cuts out contact chip (0.5 ou 1 mil): 600 sides / roll</li> <li>- Alternate clear patch 1.0 mil (full / mag cut): 600 sides / roll<sup>2</sup></li> <li>- Alternate clear patch 1.0 mil (smart cut / full): 600 sides / roll<sup>2</sup></li> <li>- Alternate clear patch 1.0 mil (smart cut / mag out): 600 sides / roll<sup>2</sup></li> <li>- Clear varnish: 1200 sides / roll</li> <li>- Holographic varnish Continuous: 1200 sides / roll</li> <li>- Holographic varnish Registered: 1200 sides / roll</li> <li>- Other films upon request</li> </ul> </li> <li>• List lamination films available on <a href="http://www.evolis.com">www.evolis.com</a></li> </ul>
<b>OPTION</b>	<ul style="list-style-type: none"> <li>• Installation of a second Card Lamination Module (CLM) to laminate both sides of the card with two different films<sup>2</sup></li> </ul>
<b>SOFTWARE</b>	<ul style="list-style-type: none"> <li>• Evolis Premium Suite®</li> </ul>
<b>CERTIFICATIONS AND STATEMENT OF COMPLIANCE</b>	<ul style="list-style-type: none"> <li>• CE, FCC, ICES, VCCI, CCC, KC, BIS</li> <li>• RoHS</li> </ul>
<b>SIZE AND WEIGHT</b>	<ul style="list-style-type: none"> <li>• CLM : <ul style="list-style-type: none"> <li>- Size (H x W x D): 269 x 205 x 370 mm (10.59" x 8.07" x 14.56")</li> <li>- Weight: 6 kg (13.22 lbs)</li> </ul> </li> <li>• With Primacy: <ul style="list-style-type: none"> <li>- Size (H x W x D): 269 x 205 x 753 mm (10.59" x 8.07" x 29.64")</li> <li>- Weight: 10 kg (22.04 lbs)</li> </ul> </li> </ul>
<b>WARRANTY<sup>3</sup></b>	<ul style="list-style-type: none"> <li>• 3-year warranty</li> <li>• Warranty extension as an option</li> </ul>

<sup>1</sup> Under specific conditions / <sup>2</sup> Available in Q4 2016  
<sup>3</sup> Warranty subject to observance of specific conditions and use of Evolis High Trust® films



### EUROPE - MIDDLE EAST - AFRICA

Evolis  
14 avenue de la Fontaine – Z.I. Angers – Beaucouzé  
49070 Beaucouzé – France  
T +33 (0) 241 367 606 – F +33 (0) 241 367 612  
[info@evolis.com](mailto:info@evolis.com)

**AMERICAS** – Evolis Inc. – Fort Lauderdale – [evolinc@evolis.com](mailto:evolinc@evolis.com)

**ASIA-PACIFIC** – Evolis Asia Pte Ltd – Singapore – [evoliasia@evolis.com](mailto:evoliasia@evolis.com)

**CHINA** – Evolis China – Shanghai – [evolischina@evolis.com](mailto:evolischina@evolis.com)

**INDIA** – Evolis India – Mumbai – [evolindia@evolis.com](mailto:evolindia@evolis.com)