



## Desktop Printers **DT4C**



**Make every second of your time counts.**

**DT4C** is ultra-light and compact for best space utilization and support multiple communication ports; it is effective and multitasking for printing applications labels and tags for retail, warehouses, logistic & transportation.



Enhanced label feeding mechanism and instant label detection.



- \* 32MB SDram and 128 MB Flash memory including 60 MB user-available memory Storage for downloadable objects.
- \* Print Speed: Up to 7" (177mm) per second
- \* Standard Interface : USB
- \* Optional Interface : Wifi, Ethernet, RS232

# Specification

# DT4C

## Desktop Printer

Model		DT4C
	<b>Print Method</b>	Direct Thermal
	<b>Resolution</b>	203 dpi (8 dots/mm)
	<b>Print Speed</b>	7 IPS (177 mm/s)**
	<b>Print Width</b>	4.25" (108 mm)
	<b>Print Length</b>	Min. 0.16" (4 mm)**; Max. 68" (1727 mm)
	<b>Processor</b>	32 Bit RISC CPU
<b>Memory</b>	<b>Flash</b>	128MB (60 MB for user storage)
	<b>SDRAM</b>	32MB
	<b>Sensor Type</b>	Adjustable reflective sensor. Fixed transmissive sensor, central aligned
<b>Media</b>	<b>Types</b>	Continuous form, gap labels, black mark sensing, and punched hole; label length set by auto sensing or programming
	<b>Width</b>	Min. 1" (25.4 mm) - Max.4.64" (118 mm)
	<b>Thickness</b>	Min. 0.003" (0.076 mm) – Max. 0.008" (0.203 mm)
	<b>Label Roll Diameter</b>	Max. 5" (127 mm)
	<b>Core Diameter</b>	1" (25.4 mm), 1.5" (38.1mm)
	<b>Printer Language</b>	EZPL, GEPL, GZPL auto switch
<b>Software</b>	<b>Label Design Software</b>	GoLabel (for EZPL only)
	<b>Driver</b>	Windows 2000, XP, Vista, Windows 7, 8.1 and 10 , Windows Server 2003 & 2008 、 MAC 、 Linux
	<b>DLL</b>	Win CE, .NET, Andriod, Windows Mobile, Windows 2000 / XP / VISTA / Windows 7 / Windows 8.1
<b>Resident Fonts</b>	<b>Bitmap Fonts</b>	6, 8, 10, 12, 14, 18, 24, 30, 16X26 and OCR A & B Bitmap fonts 90°, 180°, 270° rotatable, single characters 90°, 180°, 270° rotatable Bitmap fonts 8 times expandable in horizontal and vertical directions
	<b>TTF Fonts</b>	TTF Fonts (Bold / Italic / Underline ), 0°,90°, 180°, 270° rotatable
<b>Download Fonts</b>	<b>Bitmap Fonts</b>	90°, 180°, 270° rotatable, single characters 90°, 180°, 270° rotatable
	<b>Asian Fonts</b>	16x16, 24x24. Traditional Chinese (BIG-5), Simplified Chinese(GB2312), Japanese (S-JIS), Korean (KS-X1001) 90°, 180°, 270° rotatable and 8 times expandable in horizontal and vertical directions
	<b>TTF Fonts</b>	TTF Fonts (Bold / Italic / Underline ), 0°,90°, 180°, 270° rotatable
<b>Barcodes</b>	<b>1-D Bar codes</b>	China Postal Code, Codabar, Code 11, Code 32,Code 39, Code 93, Code 128 (subset A, B, C), EAN-8, EAN-13, EAN 8/13 (with 2 & 5 digits extension), EAN 128, FIM, German Post Code, GS1 DataBar, HIBC, Industrial 2 of 5 , Interleaved 2-of-5 (I 2 of 5), Interleaved 2- o-f 5 with Shipping Bearer Bars, ISBT – 128, ITF 14, Japanese Postnet, Logmars, MSI, Postnet, Plessey, Planet 11 & 13 digit, RPS 128, Random Weight, Standard 2 of 5, Telepen, UPC-A, UPC-E, UPC-A and UPC-E with EAN 2 or 5 digit extension, UCC 128, UCC/EAN-128 K-Mart
	<b>2-D Bar codes</b>	Aztec code, Code 49,Codablock F , Datamatrix code, MaxiCode, Micro PDF417, Micro QR code, PDF417,QR code, TLC 39
	<b>Code Pages</b>	CODEPAGE 437, 737,850, 851, 852, 855, 857, 860, 861, 862, 863, 865, 866, 869, WINDOWS 1250, 1251, 1252, 1253, 1254, 1255, 125 Unicode UTF8 、 UTF16BE 、 UTF16LE
	<b>Graphics</b>	Resident graphic file types are BMP and PCX, other graphic formats are downloadable from the software
	<b>Interfaces</b>	USB 2.0 (B-Type)
	<b>Control Panel</b>	1 Control key: FEED/PAUSE/CANCEL with dual color LED backlight: Ready(Green); Error(Red)
	<b>Power</b>	Auto Switching 100-240VAC, 50-60Hz.
<b>Environment</b>	<b>Operation Temperature</b>	41°F to 104°F (5°C to 40°C)
	<b>Storage Temperature</b>	-4°F to 140°F (-20°C to 60°C)
<b>Humidity</b>	<b>Operation</b>	25-85%, non-condensing.
	<b>Storage</b>	10-90%, non-condensing.
	<b>Agency Approvals</b>	CE (EMC) 、 FCC Class A 、 CB
<b>Dimension</b>	<b>Length</b>	8.58" (218 mm)
	<b>Height</b>	6.53" (166 mm)
	<b>Width</b>	6.61" (168 mm)
	<b>Weight</b>	3.17 lbs (1.44 Kg) ,excluding consumables
	<b>Options &amp; Accessories</b>	Cutter module Label Dispenser Wireless LAN (IEEE 802.11 b/g/n) Bluetooth Ethernet,RS232,USB host (Factory Install) Real Time Clock (RTC) External label roll holder for 10" (254 mm) O.D. label rolls External label rewinder

\* Specifications are subject to change without notice. All company and/or product names are trademarks and/or registered trademarks of their respective owners.

\*\* Minimum print height and maximum print speed specification compliance can be dependent on non-standard material variables such as label type, thickness, spacing, liner construction, etc. GoDEX is pleased to test non-standard materials for minimum print height, and maximum print speed capability.