

APEXA® GW

Versatile Powerhouse™

- Intel®'s Latest High-Performance Processors
- Ideal for Staff or Customer-Facing Applications in Retail and Hospitality Environments
 - Sleek and Compact. Small Footprint. Modern and Contemporary Styling
 - 19.5" Bezel-Free True-Flat Wide Display with PCAP Touch
 - Multiple I/O Interfaces for Peripherals
- Designed for Countertop or Wall-Mount Solutions
 - Spill and Dust Resistant
 - Faster Installation and Serviceability



GOD DESIGN




Features & Benefits



New Look. New Design

- Sleek and Compact. Small Footprint
- Modern and Contemporary Styling



Extremely Powerful Performer

- Intel® Core™ i5-6200U, Pentium® 4405U
- Intel® Celeron® J1900 Quad-Core



Superior Touch Display

- 19.5" Bezel-Free True-Flat Wide Display
- PCAP Touch, LED Backlight



Install It Anywhere

- On a Counter or a Wall
- VESA Compatible (Option)



Save Time and Cost

- Easy Access to I/O Interfaces
- Faster Installation and Serviceability



Connect It to All

- Multiple I/O Interfaces
- 6 USB, 5 Serial. Optional Expansion Available

POSBANK®

Specifications

General Specifications	
System	
Processor	Intel® Celeron® J1900 (2.0 GHz) Quad-Core Processor, Fanless Intel® Core™ i5-6200U Processor (3M Cache, 2.80 GHz) Intel® Pentium® Processor 4405U (2M Cache, 2.10 GHz)
Chipset	J1900 Intel® Bay Trail 6200U/4405U ITE Tech IT8786E
Memory	J1900 4GB Standard, DDR3L 1600 MT/s, Socket 1 x SODIMM 6200U/4405U 4GB Standard, DDR4L 2133 MT/s, Socket 1 x SODIMM (Max. 16GB)
Storage	J1900 SATA 2 (3Gb/s) 2.5 inch SSD 64GB, Support AHCI 6200U/4405U SATA 3 (6Gb/s) 2.5 inch SSD 64GB, Support AHCI
OS	Windows 7, Windows 8.1, Windows 10 IoT Enterprise, POS Ready 7
Audio	Realtek ALC662-VD
Display	
Type	19.5" Wide TFT LCD, LED Backlight
Resolution	1600 x 900
Brightness	250 cd/m ² (typ.)
Touchscreen	Projective Capacitive Touch
Interface	
Display	1 x VGA (With Power Output)
USB	J1900 6 (Rear 2, Back 4, USB 2.0 x 6) 3 (Reserved for MSR, SCR, i-Button/Touch Controller/Camera), RJ-45 6200U/4405U 6 (Rear 2, Back 4, USB 3.0 x 2, USB 2.0 x 4) 3 (Reserved for MSR, SCR, i-Button/Touch Controller/Camera), RJ-45
Serial	(COM1 with 5V/12V Power Output on 9 Pins, BIOS) (COM2-3 RJ-45, Full Signal) 5 (COM4 RJ-11, Only TX/RX, 12V Power Output, Reserved for CDP) (COM5 Reserved for Cash Drawer Port) (COM6 RJ-45, Only TX/RX, 5V Power Output, Reserved for MSR)
LAN	1 x Gigabit Ethernet, RJ-45
Audio	1 x Line-out
Power DC-IN	J1900 1 x (4 Pin Connector) 6200U/4405U 1 x (3 Pin Connector)
Extension Slot	6200U/4405U mini PCIe, m-SATA

Power	
Power Supply	J1900 Adaptor 12V, 5A 6200U/4405U Adaptor 24V, 2A / 24V, 4A(Powered USB Option)
Physical & Environmental	
Operating Temperature	0°C ~ 60°C at 10% to 90% Humidity
Storage Temperature	-20°C ~ 80°C at 10% to 90% Humidity
Dimensions (W x H x D)	490 x 337 x 210(mm), 19.3 x 13.3 x 8.2(in)
Packing Dimensions (W x H x D)	640 x 465 x 300 (mm), 25.2 x 18.3 x 11.8(in)
Net Weight	9,000g, 19.8lbs
Packing Weight	10,200g, 22.5lbs
Certification	CE, FCC, KC(TBD),CB(TBD),CCC(TBD)
Color	Matt Dark Grey, High Gloss White

Options & Peripherals	
2nd Display	9.7", 12.1", 15" LCD Display, 1024 x 768, Optional Touchscreen
Customer Display	VFD, 20 Columns x 2 Lines J1900 1 x COM5 (RJ-45 8 Pins) (Factory Option) 1 x Cash Drawer Port (Factory Option) 6200U/4405U 1 x COM5 (RJ-45 8 Pins) (Factory Option) 1 x Cash Drawer Port (Factory Option) 1 x Powered USB (24V)
I/O Expansion	Storage 2.5 inch SSD 128GB, HDD 500GB, 1TB Magnetic Stripe Reader Comply with ISO 7811, Support 1 & 2 & 3 Track Smart Card Reader EMV Level 1, 2 (TBD) Dallas Dallas i-button Reader (TBD) Fingerprint Yes Wall Mount Kit VESA-Compatible, 75 x 75(mm), 100 x 100(mm) Serial Conversion Cable RJ-45 to D-sub 9 Speaker 2 x 0.8W (Stereo) (Factory Option) WiFi J1900 USB to WiFi Module (Factory Option) 6200U/4405U USB to WiFi Module (Factory Option), Mini PCIe for Wireless LAN

*Other mounting options available upon request. *Specifications may change without prior notice.

Peripheral Options



Customer Display
• VFD (2 Lines x 20 Characters)



2nd Display
• 9.7", 12.1", 15" LCD




Multi-Reader
• MSR, SCR



POS Printers
• A7, A11

Dimension View



POSBANK®

Svensk distributör och generalagent:

Origum Distribution AB
Söderbyvägen 3 C
195 60 Arlandastad

08-410 509 50

origum@origum.se
www.origum.se

Copyright © 2017 Posbank Co.,Ltd.

Posbank and the Posbank logo are trademarks of Posbank in the United States and other countries. All trademarks are the property of their respective owners. Intel, Celeron, Core are registered trademarks of Intel Corporation in the U.S. and other countries. Microsoft, Windows 7, Windows 8.1, Windows 10 IoT Enterprise and POS Ready 7 are registered trademarks of Microsoft Corporation in the U.S. and other countries. Posbank shall not be liable for technical or editorial errors or omission contained herein. The information in this publication are informational purposes only and may be altered or amended by Posbank. All statements regarding Posbank's direction and intent are subject to change or withdraw without notice. Specifications may change without prior notice.