



1515L 15" LCD Desktop Touchmonitor

Elo's 1515L touchmonitor is designed, developed and built to provide the most cost-effective touch solutions for system integrators, and VARs. It packs Elo's quality and reliability into a integrated, affordable touchmonitor with a footprint smaller than a standard 15" display. This new cost- and space-saving touchmonitor is "designed for touch" — the technology is built into the 1515L from the ground up and not added as an afterthought by altering the original monitor. It includes a stable base, controls that are placed on the side rather than the front and are locked-out for public use. The 1515L can function as a desktop or wall-mounted unit and includes a VESA mounting option. The optional 3-track magnetic stripe reader (MSR), programmable to either HID or Keyboard Emulation (USB only), is easily installed by the user, providing an elegant, integrated solution and eliminating the need for external brackets or attachments. The display is factory sealed against dirt and dust, and the unit offers a choice of the two best touch technologies on the market today: the anti-glare clarity and superior performance of Elo's IntelliTouch surfacewave, and the company's time-tested AccuTouch five-wire resistive touch technology.

Elo's 1515L 15" LCD desktop touchmonitor provides an affordable product in a convenient, space-saving design that provides both first-time and experienced users the ability to deploy touch solutions to market easier, more reliably, and far more cost-effectively than ever before.

Features

- Up to 1020 x 768 resolution at 75 Hz
- Available with AccuTouch Five-Wire Resistive Technology (activated with fingernails, gloves, credit cards, or any stylus), IntelliTouch Surface Wave Technology for superior image quality (activated with finger or glove), or Acoustic Pulse Recognition Technology
- Optional ergonomic 3 stripe MSR available in two versions: USB with keyboard emulation; and USB with human interface device (HID) class specification 1.1
- Sealed touchscreen
- Dual serial/USB interface
- Removable base and VESA mounting option
- Mounting holes on base bottom for tabletop security
- Controls on the side, plus lockout function for public use
- Digital on-screen display (OSD)
- Internal power supply
- Worldwide agency approvals

Applications

- Point-of-sale (POS)
- Point-of-service
- Loyalty systems
- Countertop kiosk information systems



1515L 15" LCD Desktop Touchmonitor Specifications

| | |
|------------------------------|--|
| Case/Bezel Color | Dark gray and beige |
| Display Type | Active matrix TFT LCD |
| Display | Size: 15.0" diagonal Type: Active matrix TFT LCD Aspect ratio: 4 x 3 |
| Useful Screen Area | Horizontal: 12.0" (304 mm); Vertical: 9.0" (228 mm) |
| Maximum Monitor Dimensions | Width: 13.8" (350 mm) Height: (including base) 12.2" (310 mm) Depth: (including base) 6.9" (175 mm) |
| Optimal (Native) Resolution | 1024 x 768 |
| Other Supported Resolutions | 1024 x 768 at 60, 65 (Sun), 70, and 75 Hz; 832 x 624 at 75 Hz (Mac); 800 x 600 at 56, 60, 72, and 75 Hz; 720 x 400 at 70 Hz; 720 x 350 at 70 Hz; 640 x 480 at 60, 66 (Mac), 72, and 75 Hz |
| Colors | 16.2 million |
| Brightness | LCD panel: 250 cd/m ² (typical) with AccuTouch: 200 cd/m ² (typical); with Acoustic Pulse Recognition: 230 cd/m ² (typical) with IntelliTouch: 230 cd/m ² (typical) |
| Response Time | 14.2 msec (typical) |
| Viewing Angle (from center) | Horizontal (left/right): ±70° or 140° total Vertical (up/down): 55°/60° or 115° total |
| Contrast Ratio | 450:1 (typical) |
| Input Video Format | RGB analog |
| Input Sync Format | Separate H & V sync, composite sync, sync-on-green |
| Input Video Signal Connector | Mini D-Sub 15-Pin VGA type |
| Input Frequency | Horizontal: 31.5–60.2 kHz; Vertical: 56.3–75 Hz |
| Power Dissipation | 30 W maximum |
| Power Supply | Type: Internal, with jack to accept power from optional external brick Monitor Input voltage: 100-240 VAC, 50/60 Hz Optional input voltage: +12VDC ±5% |
| Options | USB Magnetic Stripe Reader |
| Temperature | Operating 0°C to 40°C Storage -20°C to 60°C |
| Humidity | Operating 20%–80%; Storage 10%–90%; noncondensing |
| Weight (approx.) | Actual: 10.6 lb (4.8 kg); Shipping: 15.4 lb (7.0 kg) |
| Warranty | Monitor: 3 years Backlight lamp life: typical 30,000 hours to half brightness MTBF: 50,000 hours demonstrated |
| Agency Approvals | UL, cUL, FCC, CE, Semko, VCCI, CI, C-Tick, MPRII, Argentina S-Mark |
| On-screen display (OSD) | Digital OSD |
| User's Controls | OSD buttons: menu, up, down, select, power; OSD: contrast, brightness, H/V position, RGB (color temp), clock, phase, recall, language (English, German, Spanish, Japanese, French); OSD disable/enable: power, OSD menu |
| Mounting Options | Removable base; 75 mm VESA mount; Threaded-through mounting holes, under base |
| Other Features | Security lock receptacle |

To find out more about Elo's extensive range of touch solutions, go to www.elotouch.com, or call the office nearest you.

North America

Elo TouchSystems
301 Constitution Drive
Menlo Park, CA 94025-1110
800-ELO-TOUCH
Tel 1-650-361-4800
Fax 1-650-361-4722
customerservice@elotouch.com

Europe

Tel +32 (0)16 35 21 00
Fax +32 (0)16 35 21 01
elosales@elotouch.com

Asia-Pacific

Tel +81 (45) 478-2161
Fax +81 (45) 478-2180
www.tps.co.jp

Latin America

Tel 786-923-0251
Fax 305-931-0124
www.elotouch.com.ar



Tyco Electronics reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products.

AccuTouch, Elo (logo), Elo TouchSystems, IntelliTouch, TE (logo) and Tyco Electronics are trademarks of the Tyco Electronics group of companies and its licensors.

Copyright 2010 Tyco Electronics Corporation 03/10

