



RT700 / RT730

Smart and Reliable Barcode Printer
for a broad range of applications

Advanced multi-purpose 4" desktop printer for light to medium duty applications. With its powerful and reliable features, RT700 is the best choice for retail and industrial applications.



Modern clam-shell design makes it simple to load labels



Rod-less label roll holder for easy loading and smooth feeding



"Twin-Sensor" technology allows you to use a broad range of labels



Innovative "C" button makes label Calibration simple and fast

Barcodes Made Easy

Model		RT700	RT730	
Print Method		Thermal Transfer/Direct Thermal		
Resolution		203 dpi (8 dots/mm)	300 dpi (12 dots/mm)	
Print Speed		5 IPS (127 mm/s)	4 IPS (102 mm/s)	
Print Width		4.25" (108 mm)	4.16" (105.7 mm)	
Print Length		Min. 0.16" (4 mm)**; Max. 68" (1727 mm)	Min. 0.16" (4 mm)**; Max. 30" (762 mm)	
Memory	Flash	8 MB Flash (4 MB for user storage)		
	SDRAM	16 MB SDRAM		
Sensor Type		Adjustable reflective sensor (full range) Fixed transmissive sensor, central aligned		
Types		Continuous form, gap labels, black mark sensing and punched hole; label length set by auto sensing or programming		
Media	Width	1" (25.4 mm) Min. - 4.64" (118 mm) Max.		
	Thickness	0.003" (0.06 mm) Min. - 0.01" (0.2 mm) Max.		
	Label Roll Diameter	Max. 5" (127 mm)		
	Core Diameter	1" (25.4 mm), 1.5" (38.1 mm)		
Ribbon	Types	Wax, wax/resin, resin		
	Length	981' (300 m)		
	Width	1.18" (30 mm) Min. - 4.33" (110 mm) Max.		
	Ribbon Roll Diameter	2.67" (68 mm)		
Printer Language		EZPL, GEPL, GZPL auto switch		
Software	Label Design Software	GoLabel (for EZPL only)		
	Driver	Windows 2000, XP, Vista, 7, Windows Server 2003 & 2008		
	DLL	Windows 2000, XP and Vista		
Resident Fonts	Bitmap Fonts	6, 8, 10, 12, 14, 18, 24, 30, 16X26 and OCR A&B Bitmap fonts 90°, 180°, 270° rotatable, single characters 90°, 180°, 270° rotatable Bitmap fonts 8 times expandable in horizontal and vertical directions		
	Scalable Fonts	90°, 180°, 270° rotatable		
Download Fonts	Bitmap Fonts	Bitmap fonts 90°, 180°, 270° rotatable, single characters 90°, 180°, 270° rotatable		
	Asian Fonts	Asian fonts 90°, 180°, 270° rotatable and 8 times expandable in horizontal and vertical directions		
Barcodes	1-D Bar codes	Code 39, Code 93, EAN 8 /13 (add on 2 & 5), UPC A/E (add on 2 & 5), I 2 of 5 & I 2 of 5 with Shipping Bearer Bars, Codabar, Code 128 (subset A, B, C), EAN 128, RPS 128, UCC 128, UCC/EAN-128 K-Mart, Random Weight, Post NET, ITF 14, China Postal Code, HIBC, MSI, Plessey, Telepen, FIM, GS1 DataBar		
	2-D Bar codes	PDF417, Datamatrix code, MaxiCode, QR code, Micro PDF417, Micro QR code, Aztec code		
Code Pages		CODEPAGE 437, 850, 851, 852, 855, 857, 860, 861, 862, 863, 865, 866, 869, 737 WINDOWS 1250, 1251, 1252, 1253, 1254, 1255, 1257 Unicode (UTF8, UTF16)		
Graphics		Resident graphic file types are BMP and PCX, other graphic formats are downloadable from the software		
Interfaces	USB 2.0		USB 2.0	USB 2.0
	Serial port: RS-232 (DB-9)		Serial port: RS-232(DB-9)	Serial port: RS-232(DB-9)
Ethernet 10/100 Mbps		Parallel port	Ethernet 10/100 Mbps	Parallel port
Control Panel		Two dual color LEDs (Ready & Status) Control key: FEED Power on/off button Calibration button		
Real Time Clock		Standard		
Power		Auto Switching 100-240VAC, 50-60Hz		
Environment	Operation Temperature	41°F to 104°F (5°C to 40°C)		
	Storage Temperature	-4°F to 122°F (-20°C to 50°C)		
Humidity	Operation	30-85%, non-condensing		
	Storage	10-90%, non-condensing		
Agency Approvals		CE(EMC), FCC Class A, CB, CCC, cUL		
Dimension	Length	11.0" (280 mm)		
	Height	7.3" (186 mm)		
	Width	8.3" (210 mm)		
Weight		6 lbs (2.72 Kg), excluding consumables		
Options		Guillotine Cutter Label Dispenser External label roll holder for 10" (250 mm) O.D. label rolls External label rewinder		

* Specifications are subject to change without notice. All company and/or product names are trademarks and/or registered trademarks of their respective owners.

** Minimum print height and maximum print speed specification compliance can be dependent on non-standard material variables such as label type, thickness, spacing, liner construction, etc. Godex is pleased to test non-standard materials for minimum print height and maximum print speed capability.