



# RT700 / RT730

Smart and Reliable Barcode Printer  
for a broad range of applications

Advanced multi-purpose 4" desktop printer for light to medium duty applications. With its powerful and reliable features, RT700 is the best choice for retail and industrial applications.



Modern clam-shell design makes it simple to load labels



Rod-less label roll holder for easy loading and smooth feeding



"Twin-Sensor" technology allows you to use a broad range of labels



Innovative "C" button makes label Calibration simple and fast

Barcodes Made Easy

Model		RT700		RT730		
<b>Print Method</b>		Thermal Transfer/Direct Thermal				
<b>Resolution</b>		203 dpi (8 dots/mm)		300 dpi (12 dots/mm)		
<b>Print Speed</b>		5 IPS (127 mm/s)		4 IPS (102 mm/s)		
<b>Print Width</b>		4.25" (108 mm)		4.16" (105.7 mm)		
<b>Print Length</b>		Min. 0.16" (4 mm)**; Max. 68" (1727 mm)		Min. 0.16" (4 mm)**; Max. 30" (762 mm)		
<b>Memory</b>	<b>Flash</b>	8 MB Flash (4 MB for user storage)				
	<b>SDRAM</b>	16 MB SDRAM				
<b>Sensor Type</b>		Adjustable reflective sensor (full range) Fixed transmissive sensor, central aligned				
<b>Types</b>		Continuous form, gap labels, black mark sensing and punched hole; label length set by auto sensing or programming				
<b>Media</b>	<b>Width</b>	1" (25.4 mm) Min. - 4.64" (118 mm) Max.				
	<b>Thickness</b>	0.003" (0.06 mm) Min. - 0.01" (0.2 mm) Max.				
	<b>Label Roll Diameter</b>	Max. 5" (127 mm)				
	<b>Core Diameter</b>	1" (25.4 mm), 1.5" (38.1 mm)				
<b>Ribbon</b>	<b>Types</b>	Wax, wax/resin, resin				
	<b>Length</b>	981' (300 m)				
	<b>Width</b>	1.18" (30 mm) Min. - 4.33" (110 mm) Max.				
	<b>Ribbon Roll Diameter</b>	2.67" (68 mm)				
<b>Printer Language</b>		EZPL, GEPL, GZPL auto switch				
<b>Software</b>	<b>Label Design Software</b>	GoLabel (for EZPL only)				
	<b>Driver</b>	Windows 2000, XP, Vista, 7, Windows Server 2003 & 2008				
	<b>DLL</b>	Windows 2000, XP and Vista				
<b>Resident Fonts</b>	<b>Bitmap Fonts</b>	6, 8, 10, 12, 14, 18, 24, 30, 16X26 and OCR A&B Bitmap fonts 90°, 180°, 270° rotatable, single characters 90°, 180°, 270° rotatable Bitmap fonts 8 times expandable in horizontal and vertical directions				
	<b>Scalable Fonts</b>	90°, 180°, 270° rotatable				
<b>Download Fonts</b>	<b>Bitmap Fonts</b>	Bitmap fonts 90°, 180°, 270° rotatable, single characters 90°, 180°, 270° rotatable				
	<b>Asian Fonts</b>	Asian fonts 90°, 180°, 270° rotatable and 8 times expandable in horizontal and vertical directions				
<b>Barcodes</b>	<b>1-D Bar codes</b>	Code 39, Code 93, EAN 8 /13 (add on 2 & 5), UPC A/E (add on 2 & 5), I 2 of 5 & I 2 of 5 with Shipping Bearer Bars, Codabar, Code 128 (subset A, B, C), EAN 128, RPS 128, UCC 128, UCC/EAN-128 K-Mart, Random Weight, Post NET, ITF 14, China Postal Code, HIBC, MSI, Plessey, Telepen, FIM, GS1 DataBar				
	<b>2-D Bar codes</b>	PDF417, Datamatrix code, MaxiCode, QR code, Micro PDF417, Micro QR code, Aztec code				
<b>Code Pages</b>		CODEPAGE 437, 850, 851, 852, 855, 857, 860, 861, 862, 863, 865, 866, 869, 737 WINDOWS 1250, 1251, 1252, 1253, 1254, 1255, 1257 Unicode (UTF8, UTF16)				
<b>Graphics</b>		Resident graphic file types are BMP and PCX, other graphic formats are downloadable from the software				
<b>Interfaces</b>	USB 2.0		USB 2.0		USB 2.0	
	Serial port: RS-232 (DB-9)		Serial port: RS-232(DB-9)		Serial port: RS-232 (DB-9)	
Ethernet 10/100 Mbps		Parallel port		Ethernet 10/100 Mbps		
<b>Control Panel</b>		Two dual color LEDs (Ready & Status) Control key: FEED Power on/off button Calibration button				
<b>Real Time Clock</b>		Standard				
<b>Power</b>		Auto Switching 100-240VAC, 50-60Hz				
<b>Environment</b>	<b>Operation Temperature</b>	41°F to 104°F (5°C to 40°C)				
	<b>Storage Temperature</b>	-4°F to 122°F (-20°C to 50°C)				
<b>Humidity</b>	<b>Operation</b>	30-85%, non-condensing				
	<b>Storage</b>	10-90%, non-condensing				
<b>Agency Approvals</b>		CE(EMC), FCC Class A, CB, CCC, cUL				
<b>Dimension</b>	<b>Length</b>	11.0" (280 mm)				
	<b>Height</b>	7.3" (186 mm)				
	<b>Width</b>	8.3" (210 mm)				
<b>Weight</b>		6 lbs (2.72 Kg), excluding consumables				
<b>Options</b>		Guillotine Cutter Label Dispenser External label roll holder for 10" (250 mm) O.D. label rolls External label rewinder				

\* Specifications are subject to change without notice. All company and/or product names are trademarks and/or registered trademarks of their respective owners.

\*\* Minimum print height and maximum print speed specification compliance can be dependent on non-standard material variables such as label type, thickness, spacing, liner construction, etc. Godex is pleased to test non-standard materials for minimum print height and maximum print speed capability.